



- TP 8포트(Combo) + SFP 1G 24슬롯 + SFP 10G 4슬롯 매니지먼트
- 4k VLAN entries, GVRP, 802.1D(STP), 802.1W(RSTP), 802.1S(MSTP)
- IGMP v1/v2/v3, IGMP Snooping , Static routing
- MLD v1/v2 , MLD Snooping)
- Port isolation, port security , DHCP Snooping
- IEEE802.1x certification, Radius , TACACS+
- Static and LACP link aggregation , EAPS , ERPS
- Console, Telnet, SSH, HTTP, HTTPS, SNMPv1/v2/v3, RMON, NTP, SPAN, RSPAN

▶ 제품 사양

표준	네트워크 프로토콜	IEEE 802.3/3u/3ab/3z 10BaseT/100BaseTX and 1000BaseT/Gigabit Fiber IEEE 802.3ad Port trunk with LACP IEEE 802.1w Rapid spanning tree protocol IEEE 802.1Q VLAN Tagging IEEE 802.1x Port Authentication Network Control
인터페이스	TP포트	10/100/1000Mbps TP 8포트(Combo)
	광포트	100/1000Mbps SFP 24슬롯 + 10Gbps SFP 4슬롯
성능	Switch Fabric	128Gbps
	Throughput	95.2Mpps
	Flash Memory	16MB
	MAC Table	16K
	Jumbo Frame	10K
동작환경	동작온도	-10°C ~ 50°C
	입력전원	AC100 ~ 240V, 50/60Hz
기타	크기	440mm(W) x 205mm(D) x 44mm(H)
	무게	3KG

▶ SFP 정보

SFP+10G-LR	10G, Single-mode, 전송거리 10km, 1310nm, LC
SFP+10G-SR	10G, Multi-mode, 전송거리 300m, 850nm, LC
SFP-LX20/SFP-SX	1G, 싱글모드, 20km, 1310nm, LC / 1G, 멀티모드, 220m, 850nm, LC
SFP-SM20/SFP-MM	100M, 싱글모드, 20km, 1310nm, LC / 10G, 멀티모드, 2km, 1310nm, LC
SFP-SMW/SFP-LXW	100M, 싱글모드, 20km, 1-Fiber(WDM) / 1G, 싱글모드, 20km, 1-Fiber(WDM)